

Features

- To replace 40, 60 watt E26/27 standard household incandescent light bulbs
- Low cost operation: 85% electricity saving compared to incandescent and greater than 40% savings compared to CFL
- Maintenance free - 20000 hours long life operation
- High energy efficiency: can reach 100lm/w
- High transmission glass cover
- IP54 rating suitable for outdoor operation
- Excellent color rendering. CRI - 90 with warm white and neutral white
- Environmentally friendly-No mercury. No lead & RoHS compliant
- UV and IR free



Product Offering

Item	Dimmable	Wattage	Input Voltage	Color Temperature
FilaLED A19	Yes	3.5W	220-240V	2200K, 2500K, 2700K, 6000K
FilaLED A19	Yes	5.5W	220-240V	2200K, 2500K, 2700K, 6000K
FilaLED A19	Yes	6.5W	220-240V	2200K, 2500K, 2700K, 6000K

Description

The new FilaLED A19 bulbs use 3.5-6.5W power to illuminate as much light as a 60W incandescent light bulb.

These energy efficient lamps save you money through reduces maintenance and electricity costs while having a positive effects on the environment. You can use it in most places where you currently use a standard incandescent bulb.

- Beam Angle: 360° full beam angle
- CCT range selection: 2200K +/- 80K, 2500K +/- 100K, 2700K, +/-150K, 6000K +/-200K
- Available in E26, E27, or B22 base

Application Information

Applications

Home lighting

Office lighting

Retail lighting

Hotel & restaurant lighting

High ceiling lighting

Industrial and commercial lighting

Notes

·Operating temperature range between -20° C and +40° C (-4° F and +104° F)

·Can be used in dry indoor and semi outdoor

·Fully TRIAC Dimmable

·Can be used in totally enclosed recessed fixtures

·Not intended for use with emergency exit fixtures or emergency lights

·Non Dimmable is not for use with dimmers or in luminaries controlled by a dimmer

Parkwell Lighting International Limited

Unit L, 7/F, Hong Kong (Chai Wan) Industrial Building, Chai Wan, Hong Kong

Tel: 36982388 Fax: 36982399 Email: info@parkwell-lighting.com



Performance Summary

Item	Dimmable	Nominal		Lumen Output	Beam Angle	CRI	PF	Housing
		Wattage	Input Voltage CCT					
FilaLED A19	Yes	3.5W	220-240VAC 2500K	350lm	360°	90	0.85	Glass
FilaLED A19	Yes	5.5W	220-240VAC 2500K	550lm	360°	90	0.85	Glass
FilaLED A19	Yes	6.5W	220-240VAC 2500K	650lm	360°	90	0.85	Glass

Note: All specifications @ 25°C ambient condition

Dimension

Lamp Type	Lamp Base	Height (mm)	Width (mm)
FilaLED A19	E26 / E27	105	60

